



Kleen-Flux 7

Our Next Generation Back-Washable Bimodal Composite Membrane Technology separates virtually all undissolved constituents down to 0.2 Micron in size consistently separating down to <10 ppm levels even in upsets with high oil and solids concentrations.

The cross-flow technology keeps the surface of the membrane KLEEN while eliminating the consumable media burden. The Bimodal membrane can be chemically clean when severe contamination is experienced where it will be regenerated and ready for reuse

Rate: 7 BPM

Max. Pressure: 150 PSI @ 150F

Tare Weight: 13,500 LB

Operating Weight (1.2SG):
17,000 LB

Dimensions: 10'0" x 8'0" x 9'6"

Deck Load: 213 PSF

Particulate Size Removal:
0.3 μ m

Number of Elements: 24

Element Type: Membrane

Specification:
ASME Code Vessels & DNV

Overpressure Protection:
PSV (Sized for Fire Case)

2720 West Willow Street
Scott, Louisiana 70583
North America 281 632 8483
International 281 632 8085

baleenprocesssolutions.com

This document is provided on an "as is" basis without warranties of any kind. BALEEN PROCESS SOLUTIONS, LLC DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR SUITABILITY FOR ANY PURPOSE, TITLE, AND NON-INFRINGEMENT. While reasonable care has been taken in the preparation of this document, Baleen Process Solutions does not represent or warrant that the contents of this document are accurate, complete, reliable, current or error-free.

© 2017 Baleen Process Solutions. All rights reserved.

Simple Solutions to Complex Water Challenges

