



## Kleen-Coalesce

Produced water polishing technology capable of removing oil droplets down to 5 micron from produced water. Automated oil recover system minimizing water in oil returns. High flux rates maximizing flow in a small footprint. Small light weight elements for easy installation.

**Rate:** 14 BPM

**Max. Pressure:**  
150 PSIG @ 250 F

**Tare Weight:** 17,820 LB

**Operating Weight (1.2 SG):**  
28,400 LB

**Dimensions:** 16'0" x 8'0" x 11'6"

**Deck Load:** 233 PSF

**Quantity:** 42

**Oil Removal:**  
5  $\mu$ m oil droplet removal

**Filter Type:** Canister

**Specification:**  
ASME Code Vessels

**Overpressure Protection:**  
PSVs (Sized for Fire Case)

2720 West Willow Street  
Scott, Louisiana 70583  
North America 281 632 8483  
International 281 632 8085

[baleenprocesssolutions.com](http://baleenprocesssolutions.com)

This document is provided on an "as is" basis without warranties of any kind. BALEEN PROCESS SOLUTIONS, LLC DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR SUITABILITY FOR ANY PURPOSE, TITLE, AND NON-INFRINGEMENT. While reasonable care has been taken in the preparation of this document, Baleen Process Solutions does not represent or warrant that the contents of this document are accurate, complete, reliable, current or error-free.

© 2018 Baleen Process Solutions. All rights reserved.

Simple Solutions to Complex Water Challenges

