



# Bulk Media Vessel

(w/Granular Activated Carbon)

	<b>BM-V2</b>	<b>BM-V5</b>
<b>Rate:</b>	2 BPM	5 BPM
<b>Max. Pressure:</b>	150 PSI	150 PSI
<b>Max Temperature:</b>	200 F	200 F
<b>Tare Weight w/Media:</b>	6,080 LB	12,600 LB
<b>Operating Weight (1.2 SG):</b>	12,600 LB	19,200 LB
<b>Dimensions:</b>	5'5" x 4'4" x 9'4"	7'3" x 6'7" x 11'
<b>Deck Loading:</b>	366 PSF	402 PSF
<b>Media Volume:</b>	2,000 LB	4,500 LB
<b>Specification:</b>	ASME Code Vessel	ASME Code Vessel
<b>Overpressure Protection:</b>	PSV (Fire Case)	PSV (Fire Case)

2720 West Willow Street  
Scott, Louisiana 70583  
North America 281 632 8483  
International 281 632 8085

[baleenprocesssolutions.com](http://baleenprocesssolutions.com)

This document is provided on an "as is" basis without warranties of any kind. BALEEN PROCESS SOLUTIONS, LLC DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR SUITABILITY FOR ANY PURPOSE, TITLE, AND NON-INFRINGEMENT. While reasonable care has been taken in the preparation of this document, Baleen Process Solutions does not represent or warrant that the contents of this document are accurate, complete, reliable, current or error-free.

© 2018 Baleen Process Solutions. All rights reserved.

Simple Solutions to Complex Water Challenges