




KLEEN
COALESCE

Kleen-Coalesce

Produced water polishing technology capable of removing oil droplets down to 5 micron from produced water. Automated oil recover system minimizing water in oil returns. High flux rates maximizing flow in a small footprint. Small light weight elements for easy installation.

Rate: 14 BPM

Max. Pressure: 150 PSIG

Max. Temperature: 250 F

Tare Weight: 17,320 LB

Operating Wt.(1.2SG): 28,400 LB

Dimensions: 16'0" x 8'0" x 11'6"

Deck Load: 222 PSF

Quantity: 42

Oil Removal: 5 μ m oil droplet removal

Filter Type: Canister

Specification: ASME Code Vessels

Overpressure Protection: PSVs (Fire Case)

2720 West Willow Street
Scott, Louisiana 70583
North America 281 632 8483
International 281 632 8085

baleenprocesssolutions.com

This document is provided on an "as is" basis without warranties of any kind. BALEEN PROCESS SOLUTIONS, LLC DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR SUITABILITY FOR ANY PURPOSE, TITLE, AND NON-INFRINGEMENT. While reasonable care has been taken in the preparation of this document, Baleen Process Solutions does not represent or warrant that the contents of this document are accurate, complete, reliable, current or error-free.

© 2018 Baleen Process Solutions. All rights reserved.

Simple Solutions to Complex Water Challenges

