



SRV-28

Rate: 28 BPM

Max. Pressure: 275PSI @ 100F
150PSI @ 220F

Tare Weight: 6,360 LB

Operating Weight (1.2 SG): 9,355 LB

Dimensions: 8'5" x 5'9" x 8'

Deck Load: 193 PSF

Quantity: 8 elements per vessel (2 vessels)

Particle Size Removal: .05 to 200 μ m

Filter Type: Cartridge or Bag

Specification: ASME Code Vessel

Overpressure Protection: PSV (Fire Case)

2720 West Willow Street
Scott, Louisiana 70583
North America 281 632 8483
International 281 632 8085

baleenprocesssolutions.com

This document is provided on an "as is" basis without warranties of any kind. BALEEN PROCESS SOLUTIONS, LLC DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR SUITABILITY FOR ANY PURPOSE, TITLE, AND NON-INFRINGEMENT. While reasonable care has been taken in the preparation of this document, Baleen Process Solutions does not represent or warrant that the contents of this document are accurate, complete, reliable, current or error-free.

© 2018 Baleen Process Solutions. All rights reserved.

Simple Solutions to Complex Water Challenges

