



KLEEN-FLUX

Kleen-Flux 2

Our Next Generation Back-Washable Bimodal Composite Membrane Technology separates virtually all undissolved constituents down to 0.2 Micron in size consistently separating down to <10 ppm levels even in upsets with high oil and solids concentrations

The cross-flow technology keeps the surface of the membrane KLEEN while eliminating the consumable media burden. The Bimodal membrane can be chemically clean when severe contamination is experienced where it will be regenerated and ready for reuse

Rate: 2 BPM
Max. Pressure: 150 PSI
Max. Temperature: 155 F
Tare Weight: 12,820 LB
Operating Wt. (1.2SG): 17,000 LB
Dimensions: 10'0" x 8'0" x 9'9"
Deck Load: 213 PSF
Number of Elements: 24
Element Type: Membrane
Specification: ASME Code Vessels & DNV
Particulate Size Removal: 0.15 µm
Overpressure Protection: PSV (Fire Case)

2720 West Willow Street
Scott, Louisiana 70583
North America 281 632 8483
International 281 632 8085

baleenprocesssolutions.com

This document is provided on an "as is" basis without warranties of any kind. BALEEN PROCESS SOLUTIONS, LLC DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR SUITABILITY FOR ANY PURPOSE, TITLE, AND NON-INFRINGEMENT. While reasonable care has been taken in the preparation of this document, Baleen Process Solutions does not represent or warrant that the contents of this document are accurate, complete, reliable, current or error-free.

© 2018 Baleen Process Solutions. All rights reserved.



Simple Solutions to Complex Water Challenges