



Desander

Baleen Process Solutions offers a variety of options for desanders that effectively remove solids from liquids using centrifugal action. No moving parts and a wide range of solids removal applications in multiphase fluid conditions.

Applications

- Produced Sand Removal upstream of boarding choke
- Well Test flowbacks
- Coiled Tubing cleanup
- Underbalanced drilling operations

	DS14	DS14 - HP
Rate:	14 BPM	14 BPM
Max. Pressure:	250 PSI @ 200 F	15,000 PSI
Tare Weight:	4,520 LB	23,000 LB
Operating Weight:	5,700 LB	24,760 LB
Dimensions:	7' x 4'4" x 9'1"	6'7" x 4'9" x 19'5"
Deck Load:	188 PSF	800 PSF
Specification:	ASME Code Vessel	API 6A NACE MRO175
Overpressure Protection:	PSV (Fire Case)	NA

2720 West Willow Street
Scott, Louisiana 70583
North America 281 632 8483
International 281 632 8085

baleenprocesssolutions.com

This document is provided on an "as is" basis without warranties of any kind. BALEEN PROCESS SOLUTIONS, LLC DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR SUITABILITY FOR ANY PURPOSE, TITLE, AND NON-INFRINGEMENT. While reasonable care has been taken in the preparation of this document, Baleen Process Solutions does not represent or warrant that the contents of this document are accurate, complete, reliable, current or error-free.

© 2018 Baleen Process Solutions. All rights reserved.

Simple Solutions to Complex Water Challenges

